Siser Heat Transfer Vinyl®

By AVERY DENNISON®

EASYPSV® APPLICATION INSTRUCTIONS

1. Place *EasyPSV* with the liner side down and cut your design. (DO NOT reverse / mirror your design.)
2. Weed the excess vinyl.
3. Remove the application tape's paper liner. Place the tape on top of *EasyPSV* and burnish with a squeegee.
4. Lift the application tape and *EasyPSV* away from the paper liner to expose the removable adhesive.
5. Place the application tape with your design on your desired object.
6. Burnish with a squeegee to fully adhere the design.
7. Gently peel away the application tape, leaving just your *EasyPSV* design on the object.

EASYPSV® STARLING™

Specifications: Smooth opaque / high gloss finish · 76 microns · 45° Blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent, Clear Acrylic
Liner	78# Bleached Kraft
Minimum, Application Temperature	10 °C
Shelf Life	2 years when stored at 20-25 °C and 50% relative humidity.
Romeo / Juliet Cut Settings	Speed: 10 / Force: 5

Dishwasher safe up to 80 washes.
Not recommended for use with microwave, or painted drywall.
Allow 72 hour dwell time after graphics application prior to placing in dishwasher.

EASYPSV® GLITTER

Specifications: Smooth gloss finish · 76 microns · 45° Blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent, Acrylic
Liner	78# Kraft
Minimum, Application Temperature	10 °C
Shelf Life	2 years when stored at 20-25 °C and 50% relative humidity.
Romeo / Juliet Cut Settings	Speed: 10 / Force: 5

Not recommended for use with dishwasher, microwave, or painted drywall.

Recommended Accessories: Cutting Machine, Siser® Weeder®, EasyPSV® Mask, Siser® Squeegee