GLITTER

SPECIFICATIONS

Composition	Av erage Thickness	Carrier	**Certifications**
PU	350 microns	Adhesive polyester	REACH compliant VEGANOK AZIENDA N. 1004

APPLICATION INSTRUCTIONS | Laser friendly

Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
cotton, polyester, poly/ cotton blends (not suited for treated and dye sublimated textiles)	60 °	120 gf	20 cm/sec	15 seconds	160 °C (320 °F)	Medium (2,5/3,5 bar)	hot/cold

→ **Mirror cut the design**
→ **Weed excess material**
→ **Place the design on the garment**
→ **Heat apply at the conditions shown above**
→ **Peel carrier hot** or cold

PRODUCT HIGHLIGHTS
→ More than 45 colours available
→ Wow effect
Perfect for trendy or fashion items

NOTE: **We highly recommend to perform a test before launching a production.**

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Dry cleaning	Storage **Shelf Life**	Storage Temperature	Storage **Conditions**	Position
Up to 40 °C, best inside-out	YES best inside-out	YES (cotton cycle)	YES	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

→ **Wait 24 hours after the application before the first wash**
→ Respect the textile recommendations
→ Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com
For further information, please contact our sales office: info@siser.it

Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it
www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 ISO 14001:2015
www.tuv.com ID 9105027958