CONFORM 4050RLA®

PAPER APPLICATION TAPE WITH RLA®

4050RLA® Conform Series® application tape is standard weight sa turated paper coated with a medium tack rubber adhesive designed spedifally as a premasking of mid-sized die cut or prespaced vinyl and printegraphics.
4050RLA® features RLA® technology with improved adhesion to paper or film release liners.

TECH DATA SHEET



PHYSICAL SPECIFICATIONS

Adhesive Rubber-based Color White/Translucent Caliper facestock 100-113 microns (4..0 -4.5 mils) Caliper facestock + adhesive 125-138 microns (5.0 - 5.5 mils) Adhesion to Steel* 13 - 15 N/100mm (12 - 14 oz.) Tensile 297 N/100mm (17lb./in) Elongation 3-4% **Tear Resistance** 50

FEATURES

Shelf Life**

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with adhesive delamination.

1 year

• Works well in either wet or dry applications with no adhesiveansfer.

APPLICATIONS

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment.

Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.



RTape Corp.
6 Ingersoll Road
South Plainfied, NJ
07080
T 1-800-440-1250
www.rtape.com

