

SERITEC® HR

SERITEC® High Resistance guarantees optimal performances when a high level of abrasion is concerned: its special formulation prevents edge corruption.

MAIN FEATURES:

- Impressive resistance to abrasion
- Good resistance to inks
- Recommended with abrasive inks
- Suggested for semi - and automatic printing

- RESISTANCE TO ABRASION
- LONGER LASTING PERFORMANCE
- OPTIMAL ON ROUGH SURFACES

SERITEC® HR squeegees are available with the following features:

HARDNESS: from 50 sh A to 95 sh A

SPECIAL SQUEEGEES: double and triple layer, 9x9, 9.5x9.5, 10x10 SQUARE PROFILE

LENGTH: mm 3660, mm 3050 or cut to size

WIDTH: from 20 mm up to 100 mm

THICKNESS: from mm 4 up to mm 10

PROFILE: PO, P1, P2, P3, P4, P5, P5A, P6, P7



It is manufactured for those aggressive screen printing applications demanding huge abrasion resistance: it has been especially conceived to print on rough surfaces or with abrasive inks (glitter, metallic,..).



MAQUINARIA, SUMINISTROS Y SERVICIO TÉCNICO
PARA PROFESIONALES DE LAS ARTES GRÁFICAS
SERIGRAFÍA · TAMPOGRAFÍA · DIGITAL · LÁSER · NARROW WEB · 3D

W W W . p e f e r s a . e s

