







Date of issue : 15/10/2008 Last. mod. date : 10/02/2009

Product code

Description

05956 RI-MARK L100 SERIES

Self adhesive material for plotter. Monomeric gloss finish vinyls, suitable for 3 years indoor/outdoor use, with good flexibility and conformability. 33 colours available.

Printable in solvent and UV screenprinting.

Permanent acrylic with excellent water resistance.

For medium term indoor & outdoor signs. Flammability DIN 752000: self-extinguishing resistance against chemicals and solvents DIN 51958. Available width 1220 mm.

Technical data

FACE MATERIAL

Type Monomeric vinyl Colour and Finish 33 available colours

 $\begin{array}{ll} Weight & 95 g/m^2 \\ Thickness & 70 \mu \end{array}$

ADHESIVE

Reference AP 900

Type Acrylic permanent

 Min. Appl. Temp.
 +10°C

 Service Temp.
 -30C/+80C

 Shear
 Very High

 Tack FTM9
 6N/inch²

 FinAdh FTM2
 9N/inch

RELEASE BACKING

Type 1 side clay-coat
Colour and Finish white, printed L&M

 $\begin{tabular}{lll} Weight & 120g/m^2 \\ Thickness & 108\mu \\ \end{tabular}$

CHEMICAL RESISTANCE

Detergent No effect (24 Hrs)
Gasoline No effect (1 Hrs)
SAE20 Motoroil No effect (24 Hrs)
10% HCI No effect (10 min)
10% NH4OH No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.